

Mesh Pool Cover Lacing Instructions

for Mesh Pool Covers made in (2) or more pieces

Please read all instructions before the installation or removal of this product.

1. With pool cover sections laid flat (as space permits) place the two sections together as they will be on the pool. Where space is limited, start lacing in flat area and bunch pool cover up as cover is laced together.

2. Start at the end with the standard 8" loop. Join the two pieces together with the snap and d-ring on the perimeter web. Push the first loop up through corresponding grommet. Continue, passing each loop through a grommet and the preceding loop.

3. Continue lacing process and cover lace with the lace flap, fastening velcro as you lace.

4. Fasten snaps and d-rings as you come to them at reinforcement straps.

5. Continue process until you get to the end. At this point tie the long loop off so it cannot slip back through the last grommet. Fasten last snap and d-ring.

6. See instructions on "**Web Ratchet for Pool Cover Lace**" on the next page. Attach webs to web ratchets with d-rings as instructed.

7. Web attachment at lace locations should be completed **before** the other attachments (d-rings) to assure proper alignment of cover and tension of these webs. (These webs at the laces should be the tightest webs on the cover).

Your lacing process is complete. Please use these instructions with your standard mesh pool cover instructions.

Begin lacing at end with **standard 8" loop**. (Other end of lace has a long, 16" loop).

2" web for insertion into web ratchet. See web ratchet instructions.

Lace Flap & Pool Cover cut away for clarity

Velcro for fastening lace flap

Snap and d-ring at intermediate reinforcement straps.

Lace Flap cut away for clarity



SALES OFFICES:
7701 Highway 41 N
EVANSVILLE, IN 47725
USA

PHONE: 812-867-2421
FAX: 812-867-1429
1-800-255-5552
EMAIL: custdiv@anchorinc.com
www.anchorinc.com

PRODUCTION FACILITY:
EVANSVILLE, IN

Web Ratchet for Pool Cover Lace

1. Drill 5/8" hole 2'-0" from pool cover's edge and at centerline of 2" web at lace.
2. To install concrete anchor, follow manufacturer's instructions.
3. Place D-ring over anchor.
4. Insert bolt with washer down through D-ring, into anchor and tighten.
5. Insert web coming from pool cover at lace into slot of ratchet spool.
6. Crank ratchet so that web has wound around spool at least one time.
7. Follow these same steps at the opposite end of the lace.
8. Tighten web until pool cover is taut across pool and evenly aligned.
9. Check ratchets and webs periodically throughout dormant season for tightness. Ratchet as necessary.

